





Model	
CHX3830SQB-2	
Features	
Controls	Mechanical push buttons
Lighting	2, 3W LED Lamps (Bulbs included)
Blower Type	650 CFM, 3 speeds
Blower Performance	Speed 1, 300 CFM, 1.0 sones
	Speed 2, 510 CFM, 3.0 sones
	Speed 3, 650 CFM, 5.0 sones
Filter Type	Baffle filters (dishwasher-safe)
Ducting	Ducted
Duct Transition	6" Round (Top)
	3 1/4" x 10" Rectangular (Top)
	3 1/4" x 10" Rectangular (Rear)
Exterior Appearance	
Stainless Steel grade	430   18-Gauge   Satin Finish #4
Electrical Requirements	
Electrical requirements	120V / 60 Hz / 232W , 2.21 A
Dimensions	
Dimensions	29 3/4" (W) x 21 11/16" (D) x 5 7/8" (H)
Accessories (optional)	
Extension Chimney Kit (ducted out)	CH1120DC-1   Wall Mount Model (WM)
Warranty	
1-year Warranty	Labour, in-home service
2-year Warranty	Parts, in-home service

Dimensions




Installation




A	Floor to ceiling Height	TBD
B	Floor to counter Top Height (standard)	36"
C	Recommended Height between cooking surface and bottom of the hood	27" min. - 30" max
D	Hood Height	5 7/8"
E	Cabinet Height	TBD

Duct transition

6" Round (Top)



3/4" X 10" (Top and Rear)



The information contained herein is based on sources that we believe to be reliable, but is not guaranteed by us, may be incomplete or may change without notice