

GLASS CANOPY WALL-MOUNT HOOD

RH30WC60GS



SIGNATURE FEATURES




LCD ELECTRONIC CONTROLS

An array of versatile options with easy-toread blue displays, including a convenient kitchen timer and fan-speed selection. The hood also features sensors that will turn the unit on automatically if it senses heat



DUAL-CENTRIFUGAL FANS

Move air quietly and quickly - up to 600 cu. ft. of air per minute.



STAINLESS STEEL FILTERS

Dishwasher-safe for easy cleaning.



HALOGEN LIGHTING

For bright illumination of the cooktop surface.

PRODUCT DIMENSIONS

29-7/16" Min. 30-1/8" Min. / 54-9/16" Max. Height (With One Cover) (With Flue Extension)

Width 29-7/8" Depth 19-11/16"

30" GLASS CANOPY WALL-MOUNT HOOD

Nominal Width	30"
Installation Type	Wall Mount
Style	Stainless Steel/Glass Canopy
Intelligent Heat Sensor	Yes
Air Discharge	Vertical
Air Delivery (CFM)	600
Blower Type	Dual Centrifugal
Electronic Controls with LCD Display	Yes
Fan Speeds	4
Sound Level (dBA)	73.8
Dual Halogen Lights	Yes
Dishwasher-Safe Stainless Steel Filters	Yes
Exhaust Duct	Convertible*
Duct Required	8" Round
ACCESSORIES	
Charcoal Filter - PN # RHCFW60GS	Ontional

Duct-Free Kit (Single Pack) - PN # RHDFW60GS

SPECIFICATIONS	
Colour –	
Stainless Steel	S
Voltage Rating	120V / 60 Hz / 15A
Connected Load (kW Rating) @ 120 Volts [‡]	0.474
Amps @ 120 Volts	3.8
Shipping Weight (Approx.)	64 Lbs.
Sones Rating	9.0

Optional

Ventilation is convertible to be either ducted outside, or recirculated inside requiring no ducting.
(Recirculated option requires use of optional Duct-Free Kit.)
For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate
ground wire. Appliance must be grounded for safe operation.

NOTE. Always consult local and national electric codes. Check local building codes for installation
requirements, as they may vary per locale. Refer to Product Installation Guide for detailed installation
instructions on the web at electroluxappliances.ca.


Specifications subject to change.

Available in:



Stainless





30" Glass Canopy Wall-Mount Hood Specifications

- Product Weight 60 Lbs.
- Wall-Mount Installation
- Ventilation system is preset to exhaust air outside. If outside ducting is not possible, optional Duct-Free Kit (PN # RHDFW60GS) is available to convert ventilation to allow air to recirculate inside. (Refer to Ducted Option Specifications for outside ventilation.)
- Sones Rating 9.0
- Voltage Rating 120V / 60 Hz / 15 Amps
- Connected Load (kW Rating) @ 120 Volts = 0.474 kW (For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @ 120 Volts = 3.8 Amps
- Always consult local and national electric codes. Check local building codes for installation requirements, as they may vary per locale.
- Minimum installation height allowed from bottom of hood to cooking surface is 24" - 30" for electric and 30" for gas. (NOT more than 36" recommended.)
- To prepare mounting surface, adequate structure and support must be provided, capable of supporting 100 lbs.

Ducted Option Specifications

- For outside ventilation.
- Exhaust Duct Required 8" round
- For most efficient airflow exhaust, use a straight run or as few elbows as possible.
- Use metallic flex ducting only to connect rigid duct directly to transitions (if allowed by code).
- Thermal breaks such as short section of nonmetallic duct, should be used in areas of extreme cold.
- Cold weather installations should have additional backdraft damper installed.
- Refer to installation instructions on web for detailed exhaust duct preparation and converting vent blower system for recirculating inside.

Note: For planning purposes only. Refer to Product Installation Guide on the web at electroluxappliances.ca for detailed instructions.

Optional Accessories

- Charcoal Filter (PN # RHCFW60GS).
- Duct-Free Kit (Single Pack) (PN # RHDFW60GS).

