

FULGOR

MILANO

600 Series 30" Dual Fuel Range

F6PDF304S1



Series

600
DUAL FUEL

Size
Main Colour
Logo
Stainless Steel Aesthetics

30"
SS
•
Professional

Cooktop

Type

GAS

Cooking Surface
Gas Type
Knobs

Black Enameled
NG (5") or LP (10")
•

Gas Cooktop Features

Electric Flame Ignition and Re-ignition
Flame out sensing
Top Mount Injectors
L.P. Conversion Kit
Dual Flame Brass Burner
Heavy Duty Cast Iron Grates
Pressure Regulator

•
•
•
•
•
•

Cooking Zones

4

Front Left

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

Rear Left

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

Front Middle

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

Rear Middle

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

Front Right

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

Rear Right

Dual Flame Burner

Power (Max/ Min) Natural Gas
Power (Max/ Min) Propane

18000 (BTU/h) - 5300W / 750 (BTU/h) - 220W
15000 (BTU/h) - 4400W / 750 (BTU/h) - 220W

FULGOR

MILANO

Oven

Type

ELECTRIC PIRO

Oven Type
Temperature Regulation

Multifunction 2 Fans (True Euro Convection)
Electronic

Functions

Pyrolytic Self-Clean with automatic door latch



•

True European Convection Bake (Multi level)



•

Convection Broil



•

Convection Roast



•

Pizza (Lower Convection)



•

Bake



•

Broil



•

Dehydrate



•

Thaw (Defrost)



•

Proof (Warm)



•

Keep warm (Warm Plus)



•

Oven Lights



•

Fast Preheat



•

Control Panel

Control type
Clock Display
Temperature Display
Function Display
Commands
Language

HAWK3TC - Electronic
White LED
White LED
White LED
6 Heavy Duty Knobs / 6 Touch Keys
English / French / Spanish

Electric Oven Features

Preset/Last used temperature memory
Preheat bar (25%, 50%, 75%, 100%)
Automatic Fast Preheat
Child Door Lock
Commands Lock
Sabbath mode
12/24 hour clock format
°C/°F

•
•
•
•
•
•
•
•

Oven Door(s)

Oven Glass Window
Door Cooling System
soft closing system
Door Hinges
Handle Style

Deep Embossed Window
4 Pane Heat Resistant Glass
•
Heavy Duty Steady Tilt
Stainless Steel Tube d30mm, Metal terminals

Oven Cavity

Gross Capacity (cuft)
Usable Capacity (cuft)
Cavity Enamel Colour
Rack Positions
Oven Lights

4.4
4.1
Black
6
3x20W Halogen

Heating Element

Broil Upper Heating Element
Upper Auxiliary Element Wattage
Concealed Bake Lower Heating Element
Convection Element Wattage

3500 W (240V)
1032W (240V)
3000 W (240V)
2x1300 W (240V)

Oven Accessories

Chromed racks
Enameled Grill set (basin + anti splash)
Telescopic chromed rack
Meat probe

2
1
1
1

Dimensions

Overall dim - width

29 3/4" (758mm)

FULGOR

MILANO

Height min/max	36 3/8" (925mm) / 38 1/2" (977mm)
Overall dim - depth	29 3/4" (756mm)
Power / Ratings (208/240 V, 60 Hz)	
KW/Amps rating at 120-240V, 60Hz	3.84kW - 16.9A
KW/Amps rating at 120-208V, 60Hz	3.54kW - 17.5A
Cable + Plug	Nema 14-50P
INSTRUCTIONS FOR USE	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR