

- Preserves up to 43 (750 ml) wine bottles
- Energy Star rated
- 2 Independently controlled dual zones
- Low e, argon gas-filled triple-paned tempered glass door with uv coating
- Signature SAPPHIRE blue interior
- Full wrapped stainless-steel exterior
- Articulating, concealed self-closing hinges with built-in door stop
- Multifunction capacitative touch electronic control
- Each zone's temperature settings range from 34 °F to 65 °F; allows for ideal preservation of any collection
- Fan-assisted cooling system allows for even temperatures, quicker cooldown times, and added efficiency
- Flush LED theater lighting can be set to display your collection for 4 or 6 hours or schedule nightlight feature
- Adaptable racking system includes 6 stainless front, full-extension racks with 5 gray wine rack inserts and 1 bottom half wine rack insert. Optional shelf inserts include tempered glass shelf inserts and/or chrome-plated wire shelf inserts making it easy to adapt to food and beverage storage needs
- Unit ships right hinged with field-reversible doors
- Stainless model includes a 1" diameter stainless steel handle with faceted standoffs (26" length)
- Panel ready model requires ¾" custom door panel and handle
- Precise zero clearance design allows for unmatched integration into any built-in setting
- 4 Independent adaptable leveling legs
- Adaptable grille accepts an integrated toe kick and allows front/back and up/down alignment with adjacent cabinetry and toe kick/plinth
- Automatic defrost

**Model Details** 

· Lock standard on stainless model







Stainless with Lock

Panel Ready

Model	Lock	Finish	Description	Shipping Weight
SW24DZSS	Yes	Stainless Steel Frame	24" Dual Zone Wine Refrigerator, Factory Installed Lock	194 lbs
SW24DZPR	No	Panel Ready Frame	24" Dual Zone Wine Refrigerator	187 lbs

Refer to page 53 for accessories

Dimensions/Weight	Detail
Product Depth	23 ¼"
Product Height	34" - 35"
Product Width	23 %"
Product Weight	164 lbs
Shipping Dimensions	26 ¾" x 27 ½" x 36 ¾"
Shipping Weight	194 lbs
Bottle Capacity	Up to 43 (750 ml) standard bottles

Integration/Panel Information*	Detail
Panel Height	30" - 31"
Panel Thickness	3/4"
Panel Width	23 %"
Maximum Panel Weight	25 lbs

<sup>\*</sup>Refer to manual for all panel and installation instructions










The Legacy Companies warrants to the original purchaser of its SAPPHIRE products that they will be free from defects in materials and workmanship for the following time periods from the date of purchase shown on the sales receipt:




Model	Details
Control Type	Electronic Capacitative Touch with OLED Screen
Indoor or Outdoor	Indoor
Built-in Installation	Inset, Frameless / Overlay and Framed Cabinet Styles
Refrigerant Type	R600a


Electrical	Details
Electrical Requirements	115 V / 60 Hz
Volt Range	104 V ~ 127 V
Electrical Service	15 amp
Running Amps	0.7 amps

Approvals – Certifications	Details
Energy Star	Yes
ETL Residential / Commercial	Yes
ETL Sanitation	Yes
Star K	Yes





\*Dimensions are the same for Panel Ready unit when %" panel applied



The Legacy Companies warrants to the original purchaser of its SAPPHIRE products that they will be free from defects in  $materials \ and \ workmanship \ for \ the \ following \ time \ periods \ from \ the \ date \ of \ purchase \ shown \ on \ the \ sales \ receipt:$