DISTINTO BUILT-IN FRIDGE



FM4BM28FBI



LED lighting



Total No Frost



Noise Level 43 (dB)



Deep-freezing



Active cooling



Integrated Installation



Extended Preservation Mode

SPECIFICATIONS

Contemporary European design

 $115^{\circ}/90^{\circ}$ opening flush hinge, allowing true integrated install

Large and legible digital display

Soft-close crisper

Soft-close large pantry drawer, adjustable temperature

Sabbath mode

Height adjustable cantilever shelves

Spill-proof glass shelves

LED lighting

Field reversible doors

3D door adjustment, for easy door panel alignment


Ultra quiet 43 dB(A)

Appliance leveling from the front

fulgor-milano.us FULGOR MILANO

28" BUILT-IN FRIDGE





CODE ID	28" BUILT-IN FRIDGE FM4BM28FBI	
	FM4BI	M28FBI
Finish	Panel Ready	
PERFORMANCES/CAPACITY		,
Cooling system	Dual Evaporator / Frost Free	
Control system	Electronic	
Energy Star Qualified	Yes	
Refrigerant	R600a	
Noise Level dB(A)	43	
Total net volume, cu. ft. (liters)	12.1 (342)	
Refrigerator net volume, cu. ft. (liters)	9.1 (257)	
Freezer net volume, cu. ft. (liters)	3 (85)	
FEATURES	- 1	,
Fridge Compartment		
Control Display	LED	
Automatic Defrost	Yes	
Interior Lighting	LED - Side walls, ceiling	
Spill-proof Shelves	3	
Crispers	1	
Extended preservation drawer	1	
Door Bins	3 (2+1 gallon rack)	
Compressor	Variable speed with inverter (VCC)	
Fan Assisted Cooling	Yes	
Freezer		-
Automatic Defrost	Yes	
Large Freezer Drawer	1	
Metal Interior Freezer Drawerer		1
DIMENSIONS/WEIGHT		
Width	27 - 11/16"	690 mm
Height	76 - 1/4"	1937 mm
Depth	21 - 5/8"	550 mm
Product Weight	496 lbs	225 kg
RECOMMENDED PANEL DIMENSIONS		, g
Fridge Panel		
Height	51 - 1/16"	1297 mm
Width	29 - 3/4"	756 mm
	Min 3/4"	Min 19 mm
Thickness	Max 1 - 1/4"	Max 32 mm
Maximum Weight	34.6 lbs	15.7 kg
Freezer Panel	5UI 0.FC	10.1 Ng
Height	28 - 11/16"	729 mm
Width	29 - 3/4"	756 mm
	Min 3/4"	Min 19 mm
Thickness	Max 1 - 1/4"	Max 32 mm
Maximum Weight	19.4 lbs	
POWER / RATINGS	19.4 IDS	8.8 kg
Dedicated Circuit, V/Amps	100 \/	- 15 A
Supply voltage, V/Hz	120 V - 15 A 120 V - 60 Hz	
Rated Current, Amps	2	
nated Guitent, Amps		

fulgor-milano.us FULGOR MILANO